

Section 1: Identification

Product Name: Glow Tint® #2 (16oz)

Product Code: PW0447601

Recommended Use: Goes on evenly and the color becomes part of the skin. Easily adjusted for deeper or lighter skin tones. Glow Tint #2, Ruddy, male or dark complexion. Glow Tint #4, warm color areas as complement to Glow Tint #2

Restrictions on Use: Professional embalmer use only; not for general consumer use.

Manufacturer: TNPC, LLC – Dallas, TX 75236

Distributed by: Pierce Companies – 4722 Bronze Way – Dallas, TX 75236 – (214) 333-4230

Emergency Phone Number: CHEMTREC – (800) 424-9300

Section 2: Hazard(s) Identification

GHS Classification:

- Flammable Liquids Category 2
- Eye Irritation Category 2A
- Specific Target Organ Toxicity, Single Exposure Category 3

Signal Word: **DANGER**

Hazard Statements:

- H225: Highly flammable liquid and vapor.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.

Precautionary Statements:

- P210: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
- P233: Keep container tightly closed.
- P240: Ground and bond container and receiving equipment.
- P241: Use explosion-proof electrical, ventilating, and lighting equipment.
- P242: Use non-sparking tools.
- P243: Take action to prevent static discharges.
- P261: Avoid breathing vapors or mists.
- P264: Wash thoroughly after handling.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves and eye protection.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312: Call a POISON CENTER or doctor if you feel unwell.
- P370+P378: In case of fire: Use dry chemical, alcohol-resistant foam, carbon dioxide, or water spray to extinguish.
- P403+P235: Store in a well-ventilated place. Keep cool.
- P501: Dispose of contents/container in accordance with local, state, and federal regulations.

Pictograms:



Section 3: Composition/Information on Ingredients

| CHEMICAL NAME | CAS NUMBER | % WEIGHT | CLASSIFICATION | Trade Secret Information: Exact % of concentration is withheld to protect Trade Secret Information. Ranges are given in accordance with 29 CFR 1910.1200(i), Appendix E |
|--------------------------------|------------|----------|--|---|
| Isopropyl Alcohol | 67-63-0 | 68-78% | Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3 | |
| Other non-hazardous components | — | 21-31% | not classified under GHS | |

Section 4: First-Aid Measures

- **Inhalation:** Move to fresh air. Keep at rest. Get medical attention if symptoms occur.
- **Skin/Eye Contact:** For skin, wash with soap and water. For eyes, rinse with water for at least 15 minutes. Remove contact lenses if easy to do. Get medical attention if irritation persists.
- **Ingestion:** Rinse mouth. Do not induce vomiting. Get medical attention if symptoms occur.
- **Symptoms/Effects:** May cause eye irritation, dizziness, drowsiness, headache, and respiratory irritation.
- **Physician Notes:** Treat symptomatically. Monitor for central nervous system effects from isopropyl alcohol exposure.

Section 5: Fire-fighting Measures

- **Suitable Extinguishing Media:** Dry chemical, alcohol-resistant foam, carbon dioxide, or water fog.
- **Unsuitable Extinguishing Media:** Do not use a direct water stream.
- **Special Hazards Arising from the Chemical:** Highly flammable liquid and vapor. Vapors may form explosive mixtures with air. Burning may produce irritating or toxic fumes.
- **Advice for Firefighters:** Wear self-contained breathing apparatus and protective clothing. Cool exposed containers with water spray. Fight fire from a safe distance.

Section 6: Accidental Release Measures

- **Personal Precautions:** Remove all ignition sources. Avoid breathing vapors. Avoid contact with skin and eyes. Wear appropriate protective equipment.
- **Emergency Procedures:** Ventilate area. Keep unnecessary and unprotected personnel away.
- **Methods and Materials for Containment:** Stop leak if safe to do so. Absorb with sand, earth, vermiculite, or other inert material.
- **Cleanup Procedures:** Collect material into suitable containers for disposal. Prevent entry into drains and waterways.

Section 7: Handling and Storage

- **Safe Handling:** Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Avoid breathing vapors. Avoid contact with eyes, skin, and clothing. Use with adequate ventilation.
- **Hygiene Measures:** Do not eat, drink, or smoke when using this product. Wash hands after handling. Remove contaminated clothing before reuse.
- **Safe Storage:** Store in a cool, dry, well-ventilated place in tightly closed containers. Keep away from ignition sources and incompatible materials.
- **Incompatibilities:** Strong oxidizers.

Section 8: Exposure Controls/Personal Protection

- **Engineering Controls:** Use adequate general ventilation. Use local exhaust if vapors or mists are generated. Provide eyewash facilities in the work area. Use explosion-proof ventilation equipment where needed.
- **Personal Protective Equipment (PPE):**
 - **Gloves:** Wear chemical-resistant gloves.
 - **Eye/Face Protection:** Wear safety glasses or chemical splash goggles.
 - **Respiratory Protection:** Not normally required under normal conditions with adequate ventilation. If vapor or mist exposure is possible or ventilation is inadequate, use appropriate respiratory protection.
 - **Skin/Body:** Wear protective clothing as needed to prevent repeated or prolonged skin contact.
- **Exposure Limits Table:**

| Component | OSHA PEL | ACGIH TLV | NIOSH REL |
|-----------------------------|-------------|---------------------------|---------------------------|
| Isopropyl Alcohol (67-63-0) | 400 ppm TWA | 200 ppm TWA; 400 ppm STEL | 400 ppm TWA; 500 ppm STEL |

Section 9: Physical and Chemical Properties

- **Appearance:** Liquid; Clear reddish-purple/red-brown solution.
- **Odor:** Alcohol-like odor.
- **Odor Threshold:** Detectable at low vapor concentration.
- **pH:** Alcohol-rich mixture; pH is limited to aqueous portion.
- **Melting Point/Freezing Point:** ~-166°F to -193°F.
- **Initial Boiling Point/Boiling Range:** ~180–187°F.

- **Flash Point:** ~54–59°F.
- **Evaporation Rate:** >1.
- **Flammability:** Flammable liquid.
- **Upper/Lower Flammability or Explosive Limits:** LEL: ~2%; UEL: ~12%.
- **Vapor Pressure:** ~35–45 mm Hg @ 68–77°F.
- **Vapor Density:** ~2.1; heavier than air.
- **Relative Density/Specific Gravity:** ~0.80–0.83 g/mL @ 68–77°F.
- **Solubility(ies):** Completely miscible with water.
- **Partition Coefficient: n-octanol/water:** Low; alcohol/water mixture remains mainly water-soluble.
- **Auto-ignition Temperature:** ~750°F.
- **Decomposition Temperature:** May decompose under high heat or fire.
- **Viscosity:** Low; thin liquid.

Section 10: Stability and Reactivity

- **Reactivity:** No dangerous reaction expected under normal use. Vapors may ignite if exposed to heat or ignition sources.
- **Chemical Stability:** Stable under normal conditions.
- **Hazardous Reactions:** Hazardous polymerization will not occur.
- **Conditions to be Avoided:** Heat, sparks, open flames, hot surfaces, and poor ventilation.
- **Incompatible Materials:** Strong oxidizers.
- **Hazardous Decomposition:** Carbon monoxide and carbon dioxide may form during fire or thermal decomposition.

Section 11: Toxicological Information

- **Likely Routes of Exposure:** Inhalation, skin contact, eye contact, and ingestion.
- **Chronic Effects:** Repeated exposure may cause eye irritation and central nervous system effects from isopropyl alcohol.
- **Acute Toxicity (LD50 & LC50):**
 - **Isopropyl Alcohol:** Oral LD50 (rat) approximately 5,045 mg/kg; Inhalation LC50 (rat, 8 hr) approximately 16,000 ppm. Causes serious eye irritation and may cause drowsiness or dizziness.
 - **Glycerine:** Low acute toxicity.
 - **Red #222 Solution:** Low concentration in the finished mixture; significant acute toxicity is not expected for the finished product.
 - **Nut Brown Shade R Solution:** Low concentration in the finished mixture; significant acute toxicity is not expected for the finished product.
- **Symptoms/Effect:** Eye irritation, dizziness, drowsiness, headache, and respiratory irritation.
- **Regulatory Listings:**
 - **NTP:** None known.
 - **IARC:** None known.
 - **OSHA:** None known.

Section 12: Ecological Information

- **Ecotoxicity:** Not expected to be highly hazardous to the aquatic environment under normal use conditions. Avoid release to drains and waterways.
- **Persistence/Degradability:** Isopropyl alcohol biodegrades readily.
- **Bioaccumulation Potential:** Isopropyl alcohol has log **Kow** approximately 0.05 and estimated **BCF** about 3, so significant bioaccumulation is not expected for the mixture.
- **Mobility in Soil:** Water-miscible components are expected to be mobile in soil and water.
- **Other Adverse Effects:** Large releases may contaminate water.

Section 13: Disposal Considerations


- Dispose of in accordance with federal, state, and local regulations.
- Empty containers must not be reused or recycled. Dispose of bottles and residual product in accordance with regulations.
- **Recommended Methods:** Incineration or chemical waste landfill.

Section 14: Transport Information

DOT (Ground Transport): Not regulated

Notes: Limited Quantity: YES (Permitted for small packaging)

Labels: Limited Quantity



IMDG (Ocean Transport):

UN#: UN1219

UN Proper Shipping Name: Isopropanol

Transport Hazard Classes: 3

Packing Group Number: II

Environmental Hazards: Marine Pollutant: No

Notes: Limited Quantity: YES (Permitted for small packaging)

Labels: Limited Quantity; Flammable Liquid (Class 3)



IATA (Air Transport):

UN#: UN1219

UN Proper Shipping Name: Isopropanol

Transport Hazard Classes: 3

Packing Group Number: II

Environmental Hazards: Marine Pollutant: No

Notes: Limited Quantity: YES (Permitted for small packaging)

Labels: Limited Quantity; Flammable Liquid (Class 3)



Section 15: Regulatory Information

TSCA List: Chemical substances are subject to TSCA inventory requirements for commercial use.

EPCRA - Emergency Planning & Community Right-to-Know: Isopropyl alcohol has a manufacturing-process qualifier under EPCRA Section 313 and is not broadly reportable in all uses. Based on the product formula, no clearly reportable Section 313 component is identified from the listed ingredients alone.

CERCLA Reportable Quantity: No CERCLA reportable quantity is assigned based on the identified components in the formula.

SARA 302: No identified components are listed as Extremely Hazardous Substances.

SARA 304 Extremely Hazardous Substances Reportable Quantity: Not applicable.

SARA 311/312: Fire hazard; eye irritation; specific target organ effects from single exposure.

SARA 313: No identified components are subject to SARA Section 313 reporting based on the listed formula and current EPA qualifier treatment for isopropyl alcohol.

California Prop 65: No identified components are known to require a Proposition 65 warning based on the listed formula provided.

US State Regulations: Isopropyl alcohol is commonly listed under state right-to-know programs, including Massachusetts, New Jersey, and Pennsylvania.

Other Regulations: Follow applicable federal, state, and local requirements for flammable-liquid storage, handling, and disposal.

Section 16: Other Information

Regulatory Compliance Verification:

This Safety Data Sheet has been prepared in accordance with and verified for compliance with:

- OSHA Hazard Communication Standard (29 CFR 1910.1200, HazCom 2023)
- Globally Harmonized System (GHS) Revision 11
- U.S. TSCA, EPCRA, CERCLA
- California Proposition 65
- Canadian WHMIS 2022 (GHS-aligned)
- EU REACH Regulation

All hazard classifications, labeling elements, and regulatory disclosures are based solely on the specific formula composition and chemical properties provided for this product.

Hazardous Material Information System III (USA)

Health: 2
Flammability: 3
Physical Hazards: 0
Personal Protection: B

National Fire Protection Association (USA)

Health: 2
Flammability: 3
Instability: 0
Special: -

HMIS ratings are based on a 0-4 scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS ratings are not required on Safety Data Sheets under 29 CFT 1910.1200, the preparer may choose to provide them. HMIS ratings are to be used with a fully implemented HMIS program. HMIS is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by: Pierce Companies Regulatory Department
Date of Preparation/Revision: March 01, 2026
Supersedes: July 01, 2024

Notice: The information in this SDS is believed to be accurate and reliable at the time of preparation, but no guarantee is made that it is complete or that the hazards listed are the only hazards present. Users are responsible for determining the suitability of the product for their intended use, complying with all applicable laws and safety requirements, and considering the effects of use with other materials. Pierce makes no express or implied warranty regarding the product, its merchantability, fitness for a particular purpose, or the accuracy of this information, except that the product will conform to Pierce's specifications. Possession of this SDS does not indicate that the holder purchased or used the product.